

LINEARlight-DRAGON Board

Rigid LED boards



- Wallwashing, cove lighting
- Ideal as recessed luminaires
- Board for luminaire installation and medium to large coving

Product features

- Total wattage 12 W at 0.5 A
- Dimmable by pulse width modulation (PWM)
- Beam angle: 170°



Technical data

Product description	Nominal voltage	Nominal wattage	Beam angle	Color temperature	Luminous flux	Light color LED
LD06B -W4F-830 ¹⁾	24.00 V	12.00 W	170 °	3000 K	630 lm	white
LD06B -W4F-840 ¹⁾	24.00 V	12.00 W	170 °	4000 K	630 lm	white
LD06B -W4F-854 ¹⁾	24.00 V	12.00 W	120 °	5400 K	630 lm	white

Product description	Length	Width	Height	Number of LEDs per module
LD06B -W4F-830 ¹⁾	300.0 mm	20.0 mm	8.5 mm	6
LD06B -W4F-840 ¹⁾	300.0 mm	20.0 mm	8.5 mm	6
LD06B -W4F-854 ¹⁾	300.0 mm	20.0 mm	8.5 mm	6

¹⁾ Modules perfectly matched to 24 V OSRAM OPTOTRONIC electronic control gear/For current photometric data and important safety, installation and application information, see www.osram.com/led-systems/All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

Equipment / Accessories

- Simplified connection with the optional CONNECTsystem
- Perfectly matched to OPTOTRONIC 24 V Electronic Control Gears

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.