

LINEARlight-DRAGON Slim

Rigid LED modules



- Shelf and furniture lighting
- Display lighting
- Small coving

Product benefits

- Low maintenance costs thanks to a lifetime of up to 50,000 h
- Robust: coated board to protect against condensate
- Adequate heat removal thanks to aluminum housing

Product features

- Slim attractive batten luminaire with six LEDs
- Diffused cover
- Adjustable
- Dimmable
- Serial connection of up to five modules on one control gear unit





Product line drawing with letters
LD06S -W4F-830 | LD06S -W4F-840

Technical data

Product description	Nominal voltage	Nominal wattage	Beam angle	Color temperature	Luminous flux	Light color LED
LD06S -W4F-830 ¹⁾	24.00 V	6.80 W	120 °	3000 K	240 lm	white
LD06S -W4F-840 ¹⁾	24.00 V	6.80 W	120 °	4000 K	240 lm	white

Product description	Length	Width	Height	Lifespan	Number of LEDs per module
LD06S -W4F-830 ¹⁾	305.0 mm ²⁾	16.0 mm	16.2 mm	50000 h	6
LD06S -W4F-840 ¹⁾	305.0 mm ²⁾	16.0 mm	16.2 mm	50000 h	6

¹⁾ Modules perfectly matched to 24 V OSRAM OPTOTRONIC electronic control gear/For current photometric data and important safety, installation and application information, see www.osram.com/led-systems/All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

²⁾ LED pitch 50 mm

Equipment / Accessories

- Mounting and connection systems included

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.